

Orchestrating a brighter world

**NEC**

**NEC ASIA PACIFIC EDITION**

# KS Series Indoor dvLED

## UNIQUE FAN-LESS DESIGN




Excellent image quality, durability and reliability marks the beginning of a new generation of digital signage. These display products include the latest technical advantages that only LED technology can deliver.



**Super Light and Slim**  
63mm , 11.5kg per panel

**Quick Installation & Fully Front Maintenance**



**Fan-less design**  
**Low power consumption**



**Fully Front Maintenance**

**Super Light and Slim**

**Fan-less design**

Model Name		KS2901	KS3901
Pixel Pitch		2.9	3.9
Physical Parameter	Pixel composition	1R1G1B	
	LED Type	3-in-1 Black SMD	
	Pixels per panel (dots)	168 x 168 / 168 x 336	128 x 128 / 128 x 256
	Cabinet size(W x H x D)mm	500 x 500 x 63 / 100 x 1000 x 63	500 x 500 x 60 / 500 x 1000 x 60
	Weight (kg)	12.5	11.5
Electronic Parameter	Refresh rate (Hz)	≥1920	≥2880
Optical Parameter	Brightness (nits)	800	900
	Contrast ratio	3000 : 1	
	Viewing angle°	H: 140° ; V : 110°	
Electrical parameter	Input voltage (V)	AC 200 ~ 240 IN, 4.6V OUT	
	Input power <max> (W/pane)	250	
	Input power <typical> (W/pane)	82	
Circumstance parameter	Storage temperature / Humidity	-20~+55/10-90%	
	Working temperature / Humidity	-10~+45/10~85%	
	Ingress protection	IP40	

**NEC ASIA PACIFIC PTE LTD**

Tel: (65) 6273 8333 | Email: [multimedia@nec.com.sg](mailto:multimedia@nec.com.sg) | Website: <http://sg.nec.com>

This document is © Copyright 2017 NEC. All rights are reserved in favour of their respective owners. The document, or parts thereof, should not be copied, adapted, redistributed, or otherwise used without the prior written permission of NEC Display Solutions. This document is provided "as is" without warranty of any kind whatsoever, either express or implied. Errors and omissions are excepted.

For more information, please visit <http://sg.nec.com>